


AGRIMAX V- FLECTO

TIRE SIZE	VF 480/60 R 28
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	145 D



DIMENSIONES IS STANDARD

SW (MM)	470	RIM REC	DW 16 L
OD (MM)	1290	RIM ALT	W 16 L
SLR (MM)	571	ECE	E11-106R-005496
RC (MM)	3807	SRI	625

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
70	1450	1685	1920	2160	2395	2635
FROM 65 TO 40	1595	1855	2115	2375	2635	2900
30	1625	1890	2155	2420	2685	2955
20	1655	1925	2195	2470	2740	3015
10	1750	2040	2325	2610	2895	3190
*UPTO 10 CYC WITH FRONT LOADER	2230	2595	2960	3325	3685	4060
10HT	1625	1890	2155	2420	2685	2955

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.