


# AS 504

<b>TIRE SIZE</b>	<b>6.00 - 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	TELESKOPLASTARE / ÅKERSLÄP / ARBETSFORDON / TELESKOPLASTARE
<b>VERSION</b>	HD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	91 A8
<b>LI/SS FREE ROLLING</b>	103 A8



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94046812	<b>RC (IN)</b>	86.2
<b>SW (IN)</b>	6.5	<b>RIM REC</b>	4.00 E
<b>OD (IN)</b>	28.9	<b>RIM ALT</b>	4.50 E; 4½ K
<b>SLR (IN)</b>	13.5	<b>ECE</b>	E11-106R-005195

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	58
5 FR	2700
15 FR	2295
20 FR	2160
25 FR	1930
5 DW	1895
15 DW	1610
20 DW	1520
25 DW	1355

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.