


# RIDEMAX IT 696

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>420/65 R 24 IND</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRATOR   |
| <b>VERSÃO</b>       | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 146 D ; 151 A8   |



## DIMENSÕES IS STANDARD

|                 |      |                |                  |
|-----------------|------|----------------|------------------|
| <b>SW (MM)</b>  | 418  | <b>RIM REC</b> | DW 13 L; W13     |
| <b>OD (MM)</b>  | 1158 | <b>RIM ALT</b> | DW 15 L; DW 14 L |
| <b>SLR (MM)</b> | 530  | <b>ECE</b>     | E11-106R-005952  |
| <b>RC (MM)</b>  | 3483 | <b>SRI</b>     | 550              |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  |
|------------|------|------|------|------|------|------|------|------|
| 65         | 1200 | 1470 | 1650 | 1950 | 2220 | 2490 | 2730 | 3000 |
| 50         | 1295 | 1590 | 1780 | 2105 | 2400 | 2690 | 2950 | 3240 |
| 40         | 1380 | 1690 | 1900 | 2245 | 2555 | 2865 | 3140 | 3450 |
| 30         | 1440 | 1765 | 1980 | 2340 | 2665 | 2990 | 3275 | 3600 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.