


AT 603

| | |
|---------------------------|--|
| TIRE SIZE | 12.5/80 - 18 |
| UM | IS STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | IMPLEMENT MACHINERY / BACKHOE LOADER / IMPLEMENTS / BACKHOE LOADER |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 135 A8 |
| LI/SS FREE ROLLING | 148 A8 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 308 | RIM REC | W 9 |
| OD (MM) | 1000 | RIM ALT | 11 |
| SLR (MM) | 448 | ECE | E11-106R-004351 |
| RC (MM) | 3027 | PR | 16 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.90 |
|------------|------|
| 10 FR | 4410 |
| 25 FR | 3750 |
| 30 FR | 3530 |
| 40 FR | 3150 |
| 10 DW | 3050 |
| 25 DW | 2595 |
| 30 DW | 2440 |
| 40 DW | 2180 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.