

# CON STAR

<b>TIRE SIZE</b>	400/70 - 24
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	КОМПАКТНЫЙ ПОГРУЗЧИК / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / КОМПАКТНЫЙ ПОГРУЗЧИК / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
<b>VERSION</b>	INDUSTRIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	158 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	395	<b>RIM REC</b>	13
<b>OD (MM)</b>	1175	<b>RIM ALT</b>	DW 12; 13 SDC; DW 13; DW 13 L; DW 14 L
<b>SLR (MM)</b>	544	<b>ECE</b>	E11-106R-003025
<b>RC (MM)</b>	3556	<b>SRI</b>	575

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>5.00</b>
40	4250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.