

# AW 708

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | 500/50 - 17   |
| <b>UM</b>                 | IS STANDARD   |
| <b>CONSTRUCTION</b>       | ⊠ BIAS  |
| <b>MACHINERY</b>          | PRESSE À PAILLE / OUTILLAGE<br>AGRICOLE / REMORQUE /<br>MOISSONNEUSE / OUTILLAGE<br>AGRICOLE / REMORQUE |
| <b>VERSION</b>            | STANDARD  |
| <b>TIRE TYPE</b>          | TL  |
| <b>LI/SS FREE ROLLING</b> | 149 A8  |



## DIMENSIONS IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 500  | <b>RIM REC</b> | 16.00          |
| <b>OD (MM)</b>  | 945  | <b>ECE</b>     | E4-106R-001813 |
| <b>SLR (MM)</b> | 416  | <b>PR</b>      | 14             |
| <b>RC (MM)</b>  | 2750 |                |                |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.80 |
|------------|------|
| 10 FR      | 4550 |
| 25 FR      | 3870 |
| 30 FR      | 3640 |
| 40 FR      | 3250 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.