

AGRIMAX RT 855

TIRE SIZE	420/80 R 46
UM	US STANDARD
MACHINERY	PULVÉRISATEUR / MACHINE À VENDANGER / TRACTEUR / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	159 D ; 170 A2



DIMENSIONS US STANDARD

CODE USA	94062065	RIM ALT	W 12
SW (IN)	16.5	ECE	E4-106R-001489
OD (IN)	72.4	TRA CODE	R1W
SLR (IN)	34.0	TREAD DEPTH (32nd)	63.63
RC (IN)	222.1	TMPH (TM/H)	1
RIM REC	W 13		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46
40	3580	4110	4720	5320	5940	6550	7080	7610	8970	9640
30	3760	4320	4960	5600	6240	6880	7440	7990	9420	10130
25	3920	4510	5170	5840	6500	7180	7760	8330	9830	10570
20	4120	4730	5430	6130	6830	7530	8150	8750	10330	11100
5	4930	5650	6490	7330	8170	9010	9740	10470	12300	13230
5 LT	4790	5510	6330	7140	7960	8770	9490	10200	12030	12930
5 HT	4120	4730	5430	6130	6830	7530	8150	8750	10330	11100

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.