

## RT 857

|                  |                    |
|------------------|--------------------|
| <b>TYRE SIZE</b> | <b>380/85 R 24</b> |
| <b>UM</b>        | US STANDARD        |
| <b>MACHINERY</b> | TRACTOR            |
| <b>VERSION</b>   | STANDARD           |
| <b>TL/TT</b>     | TL                 |
| <b>LI/SS</b>     | 131 A8/B           |

### DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94053773 | <b>RC (IN)</b> | 148.9           |
| <b>SW (IN)</b>  | 15.0     | <b>RIM REC</b> | W 12            |
| <b>OD (IN)</b>  | 49.4     | <b>RIM ALT</b> | W 13 ; W 11     |
| <b>SLR (IN)</b> | 22.3     | <b>ECE</b>     | E11-106R-002977 |

### LOAD CAPACITY (LBS/TYRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   |
|-------------|------|------|------|------|------|------|
| <b>30</b>   | 2370 | 2760 | 3140 | 3530 | 3910 | 4300 |
| <b>25</b>   | 2370 | 2760 | 3140 | 3530 | 3910 | 4300 |
| <b>20</b>   | 2540 | 2950 | 3370 | 3780 | 4200 | 4610 |
| <b>5 LT</b> | 3170 | 3690 | 4210 | 4730 | 5250 | 5760 |
| <b>5 HT</b> | 2540 | 2950 | 3370 | 3780 | 4200 | 4610 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

