

AGRIMAX V-FLECTO

TIRE SIZE	VF 600/60 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	166 D



DIMENSIONES US STANDARD

CÓDIGO USA	94059126	RC (IN)	200.0
SW (IN)	23.1	RIM REC	DW 20 B
OD (IN)	66.3	RIM ALT	DW 18 L
SLR (IN)	29.8	ECE	E11-106R-005021

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	5200	6050	7010	7860	8710	9570	10630
FROM 40 TO 25	5720	6660	7700	8640	9580	10520	11700
20	5830	6790	7850	8810	9770	10720	11920
12	5940	6920	8000	8980	9950	10930	12150
5	6280	7320	8470	9500	10530	11560	12850
*UPTO 5 CYC WITH FRONT LOADER	8000	9310	10780	12090	13400	14720	16360
5 HT	5830	6790	7850	8810	9770	10720	11920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.