

# FLOTATION 648

<b>TIRE SIZE</b>	500/55 - 20
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	138 A8/134 B
<b>LI/SS FREE ROLLING</b>	150 A8/146 B



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94039234	<b>RC (IN)</b>	124.1
<b>SW (IN)</b>	20.0	<b>RIM REC</b>	16.00
<b>OD (IN)</b>	41.7	<b>ECE</b>	E11-106R-003369
<b>SLR (IN)</b>	18.0	<b>PR</b>	12

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	29	32	35
5 FR	9290	9830	10340
10 FR	8370	8850	9300
20 FR	7430	7860	8270
25 FR	6640	7020	7390
30 FR	5970	6320	6610
5 DW	6550	6930	7290
10 DW	5890	6240	6560
20 DW	5240	5540	5830
25 DW	4670	4950	5200
30 DW	4210	4450	4670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.