

# AW 708

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | 500/50 - 17  |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       | ❖ BIAS   |
| <b>MACHINERY</b>          | ENFARDADEIRA DE FENO /<br>IMPLEMENTOS AGRÍCOLAS /<br>REBOQUE / CEIFEIRA / IMPLEMENTOS<br>AGRÍCOLAS / REBOQUE |
| <b>VERSÃO</b>             | STANDARD   |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS FREE ROLLING</b> | 154 A8   |



## DIMENSÕES IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 500  | <b>RIM REC</b> | 16.00          |
| <b>OD (MM)</b>  | 945  | <b>ECE</b>     | E4-106R-002269 |
| <b>SLR (MM)</b> | 416  | <b>PR</b>      | 18             |
| <b>RC (MM)</b>  | 2750 |                |                |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>3.60</b> |
|-------------------|-------------|
| 10 FR             | 5250        |
| 25 FR             | 4465        |
| 30 FR             | 4200        |
| 40 FR             | 3750        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.