

# RIB 774 (C)

<b>TIRE SIZE</b>	225/75 - 17.5
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	134 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94011025	<b>RC (IN)</b>	90.9
<b>SW (IN)</b>	8.7	<b>RIM REC</b>	6.75
<b>OD (IN)</b>	30.5	<b>ECE</b>	E11-106R-004657
<b>SLR (IN)</b>	14.2	<b>PR</b>	12

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>100</b>
5 FR	6550
15 FR	5570
20 FR	5240
25 FR	4670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.