

## RT 857

|                  |                    |
|------------------|--------------------|
| <b>TIRE SIZE</b> | <b>420/85 R 26</b> |
| <b>UM</b>        | US STANDARD        |
| <b>MACHINERY</b> | TRACTOR            |
| <b>VERSION</b>   | STANDARD           |
| <b>TIRE TYPE</b> | TL                 |
| <b>LI/SS</b>     | 138 A8/B           |



### ABMESSUNGEN US STANDARD

|                 |          |                                      |                                    |
|-----------------|----------|--------------------------------------|------------------------------------|
| <b>USA-CODE</b> | 94045013 | <b>RIM REC</b>                       | DW 15 L                            |
| <b>SW (IN)</b>  | 17.7     | <b>RIM ALT</b>                       | W 14 L ; W 15 L ; W 16 L ; DW 16 L |
| <b>OD (IN)</b>  | 54.1     | <b>ECE</b>                           | E11-106R-003471                    |
| <b>SLR (IN)</b> | 24.3     | <b>TRA CODE</b>                      | R1                                 |
| <b>RC (IN)</b>  | 162.0    | <b>TREAD DEPTH (32<sup>nd</sup>)</b> | 51.03                              |

### LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   |
|-------------|------|------|------|------|------|------|
| <b>30</b>   | 2870 | 3340 | 3800 | 4280 | 4740 | 5200 |
| <b>25</b>   | 2870 | 3340 | 3800 | 4280 | 4740 | 5200 |
| <b>20</b>   | 3080 | 3570 | 4080 | 4570 | 5080 | 5580 |
| <b>5 LT</b> | 3850 | 4480 | 5100 | 5730 | 6360 | 6980 |
| <b>5 HT</b> | 3080 | 3570 | 4080 | 4570 | 5080 | 5580 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.