

RT 857



RT 857



RT 857 is a tire designed for soil tillage applications. Its strong casing offers excellent durability and traction. The stubble-resistant tread compound features high cut-and-chip resistance.



	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
Ø24"	320/85 R 24 (12.4 R 24)	122 A8/B	W 11	W 10 W 9	13.0	45.4	20.8	135.8	550	STD
	380/85 R 24 (14.9 R 24)	131 A8/B	W 12	W 13 W 11	15.0	49.4	22.3	148.9	600	STD
Ø26"	420/85 R 26 (16.9 R 26)	138 A8/B	DW 15 L	W 14 L W 15 L W 16 L DW 16 L	17.7	54.1	24.3	162.0	650	STD
	460/85 R 26 (18.4 R 26)	143 A8/B	DW 15 L	W 15 L W 16 L DW 16 L	18.3	56.8	25.3	169.2	675	STD
Ø28"	320/85 R 28 (12.4 R 28)	124 A8/B	W 11	W 9 W 10	13.0	49.4	22.7	148.8	600	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
			
			
A8/B	145 lbs		

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
380/85 R 28 (14.9 R 28)	133 A8/B	W 12	W 11 W 13	15.4	53.4	24.3	162.5	650	STD
340/85 R 28 (13.6 R 28)	127 A8/B	W 12	W 11	13.9	50.7	23.6	153.9	625	STD
420/85 R 28 (16.9 R 28)	139 A8/B	W 15 L	W 14 L W 13	17.7	56.1	25.2	168.3	675	STD
Ø30"	420/85 R 30 (16.9 R 30)	W 15 L	W 14 L W 13	17.7	58.1	25.8	173.1	700	STD
	460/85 R 30 (18.4 R 30)	W 16 L	W 15 L W 14 L	18.7	60.8	27.4	183.0	725	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
			
			
			
Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index			