


AGRIMAX V-FLECTO



TIRE SIZE	VF 600/60 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	168 D

DIMENSIONS US STANDARD

USA CODE	94065356	RC (IN)	199.9
SW (IN)	23.1	RIM REC	DW 20 B
OD (IN)	66.3	RIM ALT	DW 18 L
SLR (IN)	29.8	ECE	E11-106R-006414

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	5170	5960	6860	7640	8540	9330	10450	11230
FROM 40 TO 25	5690	6550	7540	8400	9390	10250	11490	12350
20	5800	6680	7680	8560	9570	10450	11720	12590
12	5910	6800	7840	8730	9750	10660	11940	12830
5	6250	7200	8290	9240	10330	11280	12630	13580
*UPTO 5 CYC WITH FRONT LOADER	7960	9170	10550	11760	13140	14350	16080	17280
5 HT	5800	6680	7680	8560	9570	10450	11720	12590

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.