


# RIDEMAX FL 693 M

<b>TIRE SIZE</b>	500/45 R 22.5
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	AUTOBOTTE / RIMORCHIO / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	146 D ; 143 E



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94043767	<b>RC (IN)</b>	122.6
<b>SW (IN)</b>	19.8	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	40.2	<b>ECE</b>	E4-106R-000786
<b>SLR (IN)</b>	17.9		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	23	29	35	41	46	52	58
45	2200	2470	3060	3490	4030	4570	4990	5470	6010
40	2410	2710	3370	3840	4430	5030	5490	6020	6610
30	2930	3280	4090	4650	5370	6080	6650	7290	8000
25	3300	3690	4600	5220	6030	6840	7470	8190	8990
15	3820	4290	5330	6060	7010	7950	8670	9510	10450
5	4350	4880	6070	6910	7980	9050	9890	10840	11900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.