


# AGRIMAX FORCE



TIRE SIZE	IF 710/55 R 30
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CEIFEIRA / TRATOR DE ALTA POTENCIA / TRATOR
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	166 D

## DIMENSÕES IS STANDARD

SW (MM)	716	RIM REC	DW 25 B
OD (MM)	1544	ECE	E11-106R-005716
SLR (MM)	686	SRI	725
RC (MM)	4616	TRA CODE	R1W

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2215	2550	2930	3275	3660	3995	4480	4820
FROM 65 TO 40	2435	2805	3230	3600	4025	4395	4925	5300
30	2530	2915	3355	3740	4185	4570	5120	5510
20	2625	3025	3485	3885	4345	4745	5315	5720
10	3090	3560	4100	4570	5110	5580	6250	6730
UPTO 30 CYC	3165	3645	4195	4680	5230	5710	6400	6890
UPTO 15 CYC	3770	4345	5005	5580	6235	6810	7630	8215
UPTO 10 CYC	4135	4765	5490	6120	6840	7470	8370	9010
10 HT	2530	2915	3355	3740	4185	4570	5120	5510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.