

XL GRIP (T)



XL GRIP (T)

XL GRIP (E-3) best suits on/off trucks carrying heavy loads in mining applications. Its tread compound is designed to minimize cuts and punctures on harshest ground conditions. XL GRIP (E-3) offers exceptional traction and provides an extended tyre life- cycle.



	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø16"	8.25 - 16	TT	-	16	-	6.50 H	6.00 G	0		870	0	0	19,5	STD
Ø20"	12.00 - 20	TT	-	24	-	8.5	8.0	0	320	1155	545	3465	24	STD
	11.00 - 20	TT	-	18	-	8.0	7.5	0	297	1115	529	3368	24,5	STD
	12.00 - 20	TT	-	20	-	8.5	8.0	0	320	1155	545	3465	24	STD

STD: STANDARD

TECHNOLOGIES	PERFORMANCES
   	   

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION	
					REC RIM	ALT RIM								
														
12.00 - 20	TT	-	18	-	8.5	8.0	0	320	1155	545	3465	24	STD	
10.00 - 20	TT	-	18	-	7.5	7.0	0	285	1075	505	3257	22	STD	
Ø24"	12.00 - 24	TT	-	24	-	8.5	8.0	0	320	1250	585	3710	24	STD
	12.00 - 24	TL	-	20	-	8.5	8.0	0	320	1250	585	3710	24	STD
	12.00 - 24	TT	-	20	-	8.5	8.0	0	320	1250	585	3710	24	STD

STD: STANDARD



TECHNOLOGIES		PERFORMANCES	
   		   	

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026