


# EARTHMAX SR 35

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 650/65 R 25                                                                              |
| UM           | US STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | RADLADER / FAHRLADER LHD /<br>RADLADER                                                   |
| VERSION      | CUT RESISTANT COMPOUND                                                                   |
| TIRE TYPE    | TL                                                                                       |
| LI/SS        | 180 B                                                                                    |



## ABMESSUNGEN US STANDARD

|          |          |             |           |
|----------|----------|-------------|-----------|
| USA-CODE | 94058587 | RIM REC     | 19.50/2.5 |
| OD (IN)  | 59.0     | TRA CODE    | E3        |
| SLR (IN) | 26.3     | STAR RATING | ★★        |
| RC (IN)  | 176.9    |             |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 58    | 62    | 65    | 69    |
|-----------|-------|-------|-------|-------|
| 30        | 15900 | 16200 | 17200 | 17650 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.