


# AGRIMAX FORTIS

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>600/70 R 30</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRATTORE   |
| <b>VERSIONE</b>     | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 158 D ; 161 A8   |



## DIMENSIONI IS STANDARD

|                 |      |                |                  |
|-----------------|------|----------------|------------------|
| <b>SW (MM)</b>  | 611  | <b>RIM REC</b> | DW 20 B          |
| <b>OD (MM)</b>  | 1602 | <b>RIM ALT</b> | DW 18 L ; W 18 L |
| <b>SLR (MM)</b> | 724  | <b>ECE</b>     | E4-106R-001400   |
| <b>RC (MM)</b>  | 4810 | <b>SRI</b>     | 750              |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|------------|------|------|------|------|------|------|------|------|
| 65         | 2040 | 2380 | 2680 | 2975 | 3275 | 3530 | 3910 | 4250 |
| 50         | 2145 | 2505 | 2815 | 3130 | 3440 | 3710 | 4110 | 4465 |
| 40         | 2220 | 2590 | 2915 | 3240 | 3565 | 3840 | 4255 | 4625 |
| 30         | 2350 | 2740 | 3085 | 3425 | 3770 | 4060 | 4500 | 4890 |
| 10 LT      | 2735 | 3190 | 3590 | 3990 | 4390 | 4730 | 5240 | 5695 |
| 10 HT      | 2350 | 2740 | 3085 | 3425 | 3770 | 4060 | 4500 | 4890 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.