

FL 637

TIRE SIZE	520/50 R 17
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ESPALHADOR / CISTERNA MÓVEL / REBOQUE / IMPLEMENTOS AGRÍCOLAS
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	151 D ; 148 E



DIMENSÕES US STANDARD

CÓDIGO USA	94054909	RC (IN)	115.4
SW (IN)	20.3	RIM REC	16.00
OD (IN)	37.5	ECE	E11-106R-004070
SLR (IN)	16.3		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	73
45	2020	2580	3130	3550	4100	4660	5150	5630	6180	6940
40	2220	2820	3430	3880	4500	5100	5630	6160	6780	7610
30	2680	3410	4140	4700	5430	6170	6810	7460	8200	9200
25	3010	3840	4660	5280	6120	6940	7660	8390	9210	10350
20	3340	4250	5170	5860	6780	7700	8510	9310	10230	11490
15	3490	4450	5410	6140	7100	8060	8910	9740	10700	12030
5	3980	5070	6160	6990	8080	9180	10140	11100	12190	13690

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.