

# EM 934

|                     |                   |
|---------------------|-------------------|
| <b>TIRE SIZE</b>    | <b>10.00 - 20</b> |
| <b>UM</b>           | IS STANDARD       |
| <b>CONSTRUCTION</b> | ⊠ BIAS            |
| <b>MACHINERY</b>    | GRÄVMASKIN        |
| <b>VERSION</b>      | STANDARD          |
| <b>TIRE TYPE</b>    | TT                |
| <b>LI/SS</b>        | 146 B             |



## DIMENSIONER IS STANDARD

|                 |      |                 |          |
|-----------------|------|-----------------|----------|
| <b>OD (MM)</b>  | 1060 | <b>RIM ALT</b>  | 7.0; 8.0 |
| <b>SLR (MM)</b> | 500  | <b>PR</b>       | 16       |
| <b>RC (MM)</b>  | 3208 | <b>TRA CODE</b> | E2       |
| <b>RIM REC</b>  | 7.5  |                 |          |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>7.50</b> |
| 50                | 3000        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.