

AGRIMAX RT 657

TIRE SIZE	440/65 R 24
UM	US STANDARD
MACHINERY	TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	135 D ; 138 A8



ABMESSUNGEN US STANDARD

USA-CODE	94029136	RIM REC	W 14 L
SW (IN)	17.4	RIM ALT	W 13 ; W 15 L
OD (IN)	46.5	ECE	E4-106R-000616
SLR (IN)	21.2	TRA CODE	R1W
RC (IN)	139.6	TREAD DEPTH (32 nd)	56.07

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	2310	2700	3030	3370	3700	3990	4430	4810
30	2420	2830	3190	3540	3890	4200	4650	5050
25	2500	2920	3280	3650	4010	4320	4790	5200
20	2660	3110	3490	3880	4270	4600	5090	5530
5 LT	3100	3620	4070	4520	4970	5360	5940	6450
5 HT	2660	3110	3490	3880	4270	4600	5090	5530

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.