


# AGRIMAX RT 765

<b>TYRE SIZE</b>	<b>260/70 R 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	113 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	258	<b>RIM REC</b>	W 8
<b>OD (MM)</b>	872	<b>RIM ALT</b>	9 ; W 9
<b>SLR (MM)</b>	402	<b>ECE</b>	E4-106R-000640
<b>RC (MM)</b>	2639	<b>SRI</b>	425

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>50</b>	545	625	715	805	900	990	1070	1150
<b>40</b>	545	625	715	805	900	990	1070	1150
<b>30</b>	585	670	770	865	965	1065	1150	1235
<b>10 LT</b>	730	835	960	1085	1210	1330	1440	1545
<b>10 HT</b>	585	670	770	865	965	1065	1150	1235

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.