

RIDEMAX IT 696

500/70 R 24 IND**UM** US STANDARD**CONSTRUCTION**  RADIAL**MACHINERY** TRAKTÖR**VERSION** STANDARD**TIRE TYPE** TL

157 A8 ; 152 D



UNDEFINED US STANDARD

| | | | |
|-----------------|----------|----------------|-------------------|
| USA CODE | 94067862 | RC (IN) | 155.7 |
| SW (IN) | 19.8 | RIM REC | DW 16 L |
| OD (IN) | 51.6 | RIM ALT | DW 15 L ; DW 18 L |
| SLR (IN) | 23.7 | ECE | E11-106R-007051 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 17 | 23 | 29 | 35 | 41 | 46 |
|-----------|------|------|------|------|------|------|
| 40 | 3910 | 4780 | 5250 | 6180 | 6970 | 7830 |
| 30 | 4230 | 5160 | 5670 | 6680 | 7530 | 8450 |
| 25 | 4550 | 5560 | 6100 | 7190 | 8100 | 9090 |
| 20 | 4700 | 5730 | 6290 | 7430 | 8370 | 9390 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.