

FLOTATION 648

TIRE SIZE	600/55 - 26.5
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	ENFARDADEIRA DE FENO / CEIFEIRA / ESPALHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	159 A8/156 B
LI/SS FREE ROLLING	170 A8/167 B



DIMENSÕES IS STANDARD

SW (MM)	611	RIM REC	AG 20.00
OD (MM)	1354	ECE	E4-106R-002276
SLR (MM)	581	PR	16
RC (MM)	4017		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.20	2.40	2.60
10 FR	7615	8015	8400
20 FR	6855	7215	7560
30 FR	6095	6410	6720
40 FR	5440	5725	6000
50 FR	4895	5155	5450
10 DW	5560	5845	6125
20 DW	5000	5260	5515
30 DW	4445	4675	4900
40 DW	3970	4175	4375
50 DW	3575	3760	4000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.