


AGRIMAX V-FLECTO

TIRE SIZE	VF 650/60 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HOCHLEISTUNGSTRAKTOR / TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	166 D



ABMESSUNGEN US STANDARD

USA-CODE	94062119	RC (IN)	205.9
SW (IN)	25.6	RIM REC	DW 23 B
OD (IN)	68.7	RIM ALT	DW 21 B
SLR (IN)	30.5	ECE	E11-106R-005712

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	5840	6790	7750	8710	9670	10630
FROM 40 TO 25	6430	7470	8520	9580	10630	11685
20	6550	7620	8690	9770	10840	11920
12	6680	7770	8850	9950	11040	12150
5	7070	8210	9370	10530	11680	12850
*UPTO 5 CYC WITH FRONT LOADER	8990	10460	11930	13400	14870	16360
5 HT	6550	7620	8690	9770	10840	11920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.