


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>520/85 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	FELDSPRITZE / TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	155 A8/B



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	516	<b>RIM REC</b>	DW 16 L
<b>OD (MM)</b>	1849	<b>RIM ALT</b>	DW 18 L; DD 16 L
<b>SLR (MM)</b>	813	<b>ECE</b>	E4-106R-000601
<b>RC (MM)</b>	5466	<b>SRI</b>	875

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	2170	2560	2910	3255	3565	3875
40	2170	2560	2910	3255	3565	3875
30	2325	2740	3115	3490	3820	4150
10 LT	2910	3430	3900	4365	4780	5195
10 HT	2325	2740	3115	3490	3820	4150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.