


# AGRIMAX RT 600

	<b>1050/50 R 32</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BIÇERDÖVER / YAYICI / TRAKTÖR / UYGULAMALI MAKINE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	184 A8 ; 181 B



## UNDEFINED IS STANDARD

<b>SW (MM)</b>	1059	<b>RIM REC</b>	36.0 VA (multipiece)
<b>OD (MM)</b>	1863	<b>ECE</b>	E4-106R-000813
<b>SLR (MM)</b>	826	<b>SRI</b>	875
<b>RC (MM)</b>	5700		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2	3.4	3.8
50	3715	4210	5280	5860	6520	7015	7675	8250	-	-
40	4050	4590	5760	6390	7110	7650	8370	9000	-	-
30	4335	4915	6165	6840	7610	8190	8960	9630	-	-
10 LT	5430	6155	7720	8565	9530	10255	11220	12060	-	-
10 HT	4335	4915	6165	6840	7610	8190	8960	9630	-	-
10 CYC	-	6810	8725	9565	11095	11555	12645	13595	14195	15300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.