

FL 630 ULTRA

| | |
|---------------------|---|
| TIRE SIZE | 600/50 R 22.5 |
| UM | US STANDARD |
| CONSTRUCTION | |
| MACHINERY | SPREADER / TANKER / TRAILER / IMPLEMENTS |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 159 D ; 170 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94054220 | RC (IN) | 139.1 |
| SW (IN) | 24.1 | RIM REC | AG 20.00 |
| OD (IN) | 46.1 | ECE | E11-106R-003960 |
| SLR (IN) | 20.4 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|------|-------|-------|-------|-------|-------|-------|
| 45 | 2820 | 3260 | 3690 | 4450 | 5190 | 5910 | 6660 | 7340 | 8090 | 8780 |
| 40 | 3090 | 3570 | 4060 | 4890 | 5700 | 6500 | 7300 | 8070 | 8870 | 9640 |
| 30 | 3740 | 4320 | 4910 | 5950 | 6890 | 7880 | 8820 | 9740 | 10750 | 11670 |
| 25 | 4230 | 4890 | 5560 | 6700 | 7800 | 8930 | 10040 | 11070 | 12170 | 13230 |
| 15 | 4880 | 5640 | 6400 | 7740 | 8990 | 10310 | 11490 | 12790 | 14030 | 15240 |
| 5 | 5560 | 6430 | 7300 | 8820 | 10250 | 11740 | 13090 | 14550 | 15970 | 17360 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.