


AGRIMAX FORTIS

| | |
|--------------|--|
| TIRE SIZE | 600/70 R 30 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRATOR |
| VERSÃO | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 158 D ; 161 A8 |



DIMENSÕES US STANDARD

| | | | |
|------------|----------|---------|-----------------|
| CÓDIGO USA | 94058914 | RC (IN) | 189.4 |
| SW (IN) | 24.1 | RIM REC | DW 20 B |
| OD (IN) | 63.1 | RIM ALT | DW 18 L; W 18 L |
| SLR (IN) | 28.5 | ECE | E4-106R-001400 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-----------|------|------|------|------|------|-------|-------|-------|
| 40 | 4500 | 5250 | 5910 | 6560 | 7220 | 7780 | 8620 | 9370 |
| 30 | 4730 | 5520 | 6210 | 6900 | 7580 | 8180 | 9060 | 9840 |
| 25 | 4890 | 5710 | 6430 | 7140 | 7860 | 8470 | 9380 | 10200 |
| 20 | 5180 | 6040 | 6800 | 7550 | 8310 | 8950 | 9920 | 10780 |
| 5 LT | 6030 | 7030 | 7910 | 8800 | 9680 | 10430 | 11550 | 12550 |
| 5 HT | 5180 | 6040 | 6800 | 7550 | 8310 | 8950 | 9920 | 10780 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.