

# RIDEMAX FL 690

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>28L R 26</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | АВТОЦИСТЕРНА / ПРИЦЕП /<br>СЕЛЬСКОХОЗЯЙСТВЕННОЕ<br>ОБОРУДОВАНИЕ / ПРИЦЕП                 |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 176 A8 ; 173 B   |



## РАЗМЕРЫ US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94034321 | <b>RC (IN)</b> | 186.8           |
| <b>SW (IN)</b>  | 28.3     | <b>RIM REC</b> | DW 25 B         |
| <b>OD (IN)</b>  | 62.6     | <b>RIM ALT</b> | DW 23 B         |
| <b>SLR (IN)</b> | 27.4     | <b>ECE</b>     | E11-106R-002985 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12    | 15    | 20    | 23    | 29    | 35    | 41    |
|-----------|-------|-------|-------|-------|-------|-------|-------|
| 30        | 6880  | 7850  | 9530  | 10320 | 11750 | 13040 | 14330 |
| 25        | 7520  | 8560  | 10420 | 11280 | 12840 | 14250 | 15650 |
| 20        | 8420  | 9600  | 11670 | 12630 | 14380 | 15960 | 17540 |
| 15        | 8950  | 10200 | 12390 | 13410 | 15280 | 16950 | 18630 |
| 5         | 10530 | 11990 | 14580 | 15780 | 17980 | 19950 | 21910 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.