

# TF 8181

|                     |   |
|---------------------|---|
|                     | <b>5.00 - 15</b>                        |
| <b>UM</b>           | US STANDARD                             |
| <b>CONSTRUCTION</b> | ⊠ BIAS                                  |
| <b>MACHINERY</b>    | TEK ÇEKER TRAKTÖR / TRAKTÖR /<br>RÖMORK |
| <b>VERSION</b>      | SPECIAL                                 |
| <b>TIRE TYPE</b>    | TT                                      |
|                     | 76 A8                                   |



## UNDEFINED US STANDARD

|                 |          |                |                   |
|-----------------|----------|----------------|-------------------|
| <b>USA CODE</b> | 94043903 | <b>RC (IN)</b> | 76.8              |
| <b>SW (IN)</b>  | 5.6      | <b>RIM REC</b> | 4.00 E            |
| <b>OD (IN)</b>  | 25.8     | <b>RIM ALT</b> | 3.00 D; 4 J; 4½ J |
| <b>SLR (IN)</b> | 12.1     | <b>ECE</b>     | E11-106R-005213   |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>60</b> |
| 25               | 880       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.