

AGRIMAX RT 600

| | |
|---------------------|--|
| TIRE SIZE | IF 710/75 R 34 CFO |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | CEIFEIRA / ESPALHADOR / TRATOR / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 184 A8/B |



DIMENSÕES US STANDARD

| | | | |
|-------------------|----------|----------------|------------------|
| CÓDIGO USA | 94512317 | RC (IN) | 227.2 |
| SW (IN) | 28.1 | RIM REC | DW25 B |
| OD (IN) | 75.6 | RIM ALT | DW23 B |
| SLR (IN) | 33.7 | ECE | E11-106R-0010577 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 | 41 | 46 |
|--------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 7740 | 9130 | 10520 | 11710 | 13090 | 14290 | 15670 | 16860 | 18450 | 19840 |
| 25 | 7740 | 9130 | 10520 | 11710 | 13090 | 14290 | 15670 | 16860 | 18450 | 19840 |
| 10 | 8910 | 10500 | 12100 | 13470 | 15070 | 16430 | 18030 | 19400 | 21230 | 22820 |
| 5 | 9830 | 11600 | 13360 | 14870 | 16630 | 18140 | 19910 | 21430 | 23430 | 25200 |
| UPTO 20 CYC | 10060 | 11870 | 13680 | 15220 | 17030 | 18570 | 20380 | 21920 | 24000 | 25790 |
| UPTO 10 CYC | 12000 | 14150 | 16300 | 18150 | 20300 | 22140 | 24300 | 26150 | 28600 | 30750 |
| UPTO 5 CYC | 13160 | 15520 | 17880 | 19910 | 22270 | 24290 | 26650 | 28670 | 31370 | 33730 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.