


# AS 504

<b>TIRE SIZE</b>	<b>7.00 - 12</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ELEVADOR TELESCÓPICO / EWMOLQUE PARA CAMPOS / MAQUINARIA AGRÍCOLA / ELEVADOR TELESCÓPICO
<b>VERSIÓN</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	88 A8
<b>LI/SS FREE ROLLING</b>	100 A8



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	187	<b>RIM REC</b>	4.5
<b>OD (MM)</b>	683	<b>ECE</b>	E11-106R-003382
<b>SLR (MM)</b>	311	<b>PR</b>	8
<b>RC (MM)</b>	2049		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.30
10 FR	1120
25 FR	950
30 FR	895
40 FR	800
10 DW	785
25 DW	665
30 DW	625
40 DW	560

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.