


# RIDEMAX IT 697 (M+S)

<b>TIRE SIZE</b>	<b>460/70 R 24 IND</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTEUR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	157 A8 ; 152 D



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	465	<b>RIM REC</b>	DW 15 L
<b>OD (MM)</b>	1254	<b>RIM ALT</b>	DW14 L; DW 16L
<b>SLR (MM)</b>	571	<b>ECE</b>	E11-106R-006840
<b>RC (MM)</b>	3772	<b>SRI</b>	600

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2
65	1775	2170	2380	2805	3160	3550
50	1920	2340	2570	3030	3415	3835
40	2065	2520	2765	3260	3675	4125
30	2130	2600	2855	3370	3795	4260

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.