

# AS 504

**11.5/80 - 15.3****UM** US STANDARD**CONSTRUCTION**  BIAS**MACHINERY** TELESKOPIK YÜKLEYİCİ / TARLA  
RÖMORKU / UYGULAMALI MAKİNE /  
TELESKOPIK YÜKLEYİCİ**VERSION** STANDARD**TIRE TYPE** TL

123 A8

135 A8



## UNDEFINED US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94018727 | <b>RC (IN)</b> | 100.0          |
| <b>SW (IN)</b>  | 11.4     | <b>RIM REC</b> | 9.00           |
| <b>OD (IN)</b>  | 34.1     | <b>ECE</b>     | E4-106R-001894 |
| <b>SLR (IN)</b> | 15.0     | <b>PR</b>      | 12             |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 59   |
|-----------|------|
| 5 FR      | 6720 |
| 15 FR     | 5720 |
| 20 FR     | 5380 |
| 25 FR     | 4810 |
| 5 DW      | 4780 |
| 15 DW     | 4070 |
| 20 DW     | 3820 |
| 25 DW     | 3420 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.