

# FLOTATION 558

<b>TIRE SIZE</b>	<b>400/55 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊗ BIAS
<b>MACHINERY</b>	PRESSA PER BALLE DI FIENO / MIETITREBBIA / AUTOBOTTE / RIMORCHIO / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	144 A8/140 B
<b>LI/SS FREE ROLLING</b>	156 A8/152 B



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94058501	<b>RC (IN)</b>	121.4
<b>SW (IN)</b>	15.9	<b>RIM REC</b>	AG 11.75
<b>OD (IN)</b>	40.2	<b>RIM ALT</b>	12.25; 13.00; AG 13.00
<b>SLR (IN)</b>	17.5	<b>ECE</b>	E11-106R-005351

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	67	70	73
<b>5 FR</b>	11760	12050	12350
<b>10 FR</b>	10580	10850	11110
<b>20 FR</b>	9400	9640	9880
<b>25 FR</b>	8400	8610	8820
<b>30 FR</b>	7560	7750	7830
<b>5 DW</b>	8220	8440	8640
<b>10 DW</b>	7410	7590	7780
<b>20 DW</b>	6580	6760	6910
<b>25 DW</b>	5870	6030	6170
<b>30 DW</b>	5290	5420	5510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.