


MULTIMAX MP 522

TIRE SIZE	480/80 R 26 IND
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER
VERSION	STANDARD
TL/TT	TL
LI/SS	167 A8/B



DIMENSIONS US STANDARD

USA CODE	94073108	RC (IN)	168.8
SW (IN)	18.9	RIM REC	DW 15 L
OD (IN)	56.2	RIM ALT	DW 16 L
SLR (IN)	25.1	ECE	E11-106R-008146

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64
30	5680	6210	6730	7260	7800	8330	8860	9390	9920	10450	10970	11500	12010	-	-
25	5680	6210	6730	7260	7800	8330	8860	9390	9920	10450	10970	11500	12010	-	-
20	6150	6710	7270	7830	8390	8950	9510	10060	10630	11190	11750	12300	12860	-	-
15	6370	6960	7540	8110	8700	9280	9870	10440	11020	11610	12180	12760	13340	-	-
5 CYC.	7050	7840	8620	9400	10180	10970	11750	12530	13320	14100	14880	16450	18020	-	-
STATIC	10800	12000	13200	14410	15610	16810	18010	19210	20410	21620	22820	24020	25230	26430	27630

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.