


RIDEMAX FL 693 M



TIRE SIZE	VF 400/45 R 17.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TANKER / TRAILER / IMPLEMENTS
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	159 D

DIMENSIONS US STANDARD

USA CODE	94063598	RC (IN)	92.8
SW (IN)	15.7	RIM REC	14.00
OD (IN)	31.5	ECE	E11-106R-006068
SLR (IN)	13.5		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	23	29	35	41	46	52	58	73	87
45	2200	2820	3520	3960	4570	5190	5720	6240	6860	7740	8780
40	2410	3090	3860	4340	5020	5700	6270	6860	7530	8490	9640
30	2920	3740	4670	5260	6070	6890	7590	8290	9120	10270	11670
25	3280	4200	5250	5910	6820	7750	8530	9310	10240	11550	13120
20	3650	4670	5830	6560	7580	8600	9480	10350	11380	12830	14570
15	3810	4880	6110	6870	7940	8990	9910	10820	11890	13430	15240
5	4340	5560	6940	7810	9030	10250	11290	12330	13550	15280	17360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.