


# RIDEMAX FROST

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>540/80 R 38 IND</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR  |
| <b>VERSION</b>      | STEEL BELTED   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 172 A8 ; 167 D   |



## ABMESSUNGEN IS STANDARD

|                 |      |                |                  |
|-----------------|------|----------------|------------------|
| <b>SW (MM)</b>  | 550  | <b>RIM REC</b> | DW 18 L          |
| <b>OD (MM)</b>  | 1835 | <b>RIM ALT</b> | DW 16 L          |
| <b>SLR (MM)</b> | 842  | <b>ECE</b>     | E11-106R-0010575 |
| <b>RC (MM)</b>  | 5591 | <b>SRI</b>     | 875              |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8  | 1.2  | 1.6  | 2.0  | 2.4  | 2.6  | 2.8  | 3.0  | 3.2  |
|------------|------|------|------|------|------|------|------|------|------|
| 65         | 2400 | 3165 | 3815 | 4200 | 4470 | 4690 | 4905 | 5180 | 5450 |
| 50         | 2595 | 3420 | 4125 | 4540 | 4830 | 5070 | 5305 | 5600 | 5890 |
| 40         | 2775 | 3655 | 4410 | 4855 | 5170 | 5420 | 5670 | 5985 | 6300 |
| 30         | 2880 | 3795 | 4580 | 5040 | 5365 | 5625 | 5890 | 6215 | 6540 |
| 20         | 3025 | 3985 | 4810 | 5290 | 5635 | 5910 | 6185 | 6530 | 6870 |
| 10         | 3455 | 4555 | 5495 | 6045 | 6440 | 6755 | 7065 | 7460 | 7850 |
| 5          | 4010 | 5285 | 6375 | 7015 | 7470 | 7835 | 8195 | 8650 | 9105 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.