


AGRIMAXFACTOR

TIRE SIZE	380/70 R 20
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SKÖRDEMASKIN / ARBETSFORDON / TRAKTOR / SKÖRDEMASKIN FÖR VINGÅRD
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	132 D ; 135 A8



DIMENSIONER IS STANDARD

SW (MM)	380	RIM REC	W 12
OD (MM)	1080	RIM ALT	W 11; W 13
SLR (MM)	484	ECE	E11-106R-0011740
RC (MM)	3223	TRA CODE	R1W

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	820	960	1100	1240	1380	1500	1780	2000
50	865	1010	1155	1305	1450	1575	1870	2100
40	895	1050	1200	1355	1505	1635	1945	2180
30	945	1105	1265	1430	1590	1725	2050	2300
10 LT	1100	1290	1475	1665	1850	2010	2390	2680
10 HT	945	1105	1265	1430	1590	1725	2050	2300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.