


# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>650/75 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPRAYER / TRACTOR / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	169 D



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	655	<b>RIM REC</b>	DW 21 B
<b>OD (MM)</b>	1941	<b>RIM ALT</b>	DW 20 B; DW 23 B
<b>SLR (MM)</b>	874	<b>ECE</b>	E11-106R-006161
<b>RC (MM)</b>	5820	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	2730	3135	3600	4060	4525	4990	5455	5800
50	2865	3290	3780	4265	4755	5240	5725	6090
40	2990	3435	3945	4450	4960	5470	5975	6355
30	3135	3605	4140	4670	5205	5740	6270	6670
10 LT	3655	4200	4825	5445	6065	6690	7310	7775
10 HT	3135	3605	4140	4670	5205	5740	6270	6670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.