


FL 639

| | |
|---------------------|--|
| TIRE SIZE | 710/40 R 22.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MAȘINĂ DE ÎMPRĂȘTIAT / MAȘINI DE IMPLEMENTARE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 161 D ; 172 AB |



DIMENSIUNI US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94041176 | RC (IN) | 137.5 |
| SW (IN) | 28.6 | RIM REC | AG 24.00 |
| OD (IN) | 44.9 | ECE | E4-106R-000801 |
| SLR (IN) | 19.8 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|------|-------|-------|-------|-------|-------|-------|
| 45 | 2980 | 3440 | 3900 | 4740 | 5480 | 6320 | 7150 | 7700 | 8540 | 9280 |
| 40 | 3260 | 3780 | 4290 | 5200 | 6020 | 6930 | 7860 | 8470 | 9380 | 10200 |
| 30 | 3960 | 4570 | 5190 | 6300 | 7290 | 8400 | 9510 | 10250 | 11360 | 12350 |
| 25 | 4440 | 5140 | 5830 | 7080 | 8190 | 9440 | 10680 | 11520 | 12760 | 13870 |
| 15 | 5160 | 5970 | 6780 | 8220 | 9510 | 10970 | 12410 | 13380 | 14840 | 16110 |
| 5 | 5870 | 6800 | 7720 | 9370 | 10840 | 12490 | 14140 | 15230 | 16890 | 18350 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.