

# EARTHMAX SR 42

|                  |                        |
|------------------|------------------------|
| <b>TIRE SIZE</b> | <b>14.00 R 24</b>      |
| <b>UM</b>        | US STANDARD            |
| <b>MACHINERY</b> | HAUL TRAIN             |
| <b>VERSION</b>   | CUT RESISTANT COMPOUND |
| <b>TL/TT</b>     | TL                     |
| <b>LI/SS</b>     | 171 B                  |



## DIMENSIONS US STANDARD

|                 |          |                    |        |
|-----------------|----------|--------------------|--------|
| <b>USA CODE</b> | 94067138 | <b>RIM REC</b>     | 10.00W |
| <b>OD (IN)</b>  | 55.6     | <b>RIM ALT</b>     | --     |
| <b>SLR (IN)</b> | 25.7     | <b>TRA CODE</b>    | E4     |
| <b>RC (IN)</b>  | 166.6    | <b>STAR RATING</b> | ★★★    |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>102</b> | <b>116</b> |
|------------------|------------|------------|
| 30               | 12800      | 13600      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.