


# AGRIMAX TERIS

<b>TIRE SIZE</b>	<b>620/75 R 26 CHO</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SKÖRDEMASKIN / BOMULLSMASKIN
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	166 A8/B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94035809	<b>RC (IN)</b>	191.0
<b>SW (IN)</b>	24.6	<b>RIM REC</b>	DW 20 B
<b>OD (IN)</b>	62.6	<b>ECE</b>	E4-106R-001419
<b>SLR (IN)</b>	28.7		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	20	23	29	35	41	46
<b>30</b>	5380	6190	7590	8300	9120	9930	10760	11680
<b>25</b>	5380	6190	7590	8300	9120	9930	10760	11680
<b>20</b>	5760	6640	8130	8880	9770	10640	11520	12510
<b>10 CYC</b>	8870	10220	12530	13690	15050	16390	17750	19280
<b>5 CYC</b>	9680	11150	13680	14940	16410	17880	19360	21030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.