

# FLOTATION TR 675

<b>TIRE SIZE</b>	<b>500/60 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	145 A8/142 B
<b>LI/SS FREE ROLLING</b>	157 A8/154 B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94019786	<b>RC (IN)</b>	141.9
<b>SW (IN)</b>	20.3	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	46.5	<b>RIM ALT</b>	15.00; 17.00
<b>SLR (IN)</b>	21.3	<b>ECE</b>	E4-106R-002314

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	29	35
5 FR	9680	11450	12730
10 FR	8710	10310	11460
20 FR	7740	9160	10180
25 FR	6910	8180	9090
30 FR	6220	7360	8270
5 DW	6800	8040	8950
10 DW	6130	7230	8060
20 DW	5450	6440	7160
25 DW	4860	5740	6390
30 DW	4380	5170	5840

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.