


# FL 695

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>650/55 R 26.5</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | REMORCĂ / MAȘINI DE<br>IMPLEMENTARE / REMORCĂ  |
| <b>VERSION</b>      | STEEL BELTED   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 178 D  |



## DIMENSIUNI US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94067886 | <b>RC (IN)</b> | 167.0           |
| <b>SW (IN)</b>  | 24.8     | <b>RIM REC</b> | AG20.00         |
| <b>OD (IN)</b>  | 54.7     | <b>RIM ALT</b> | AG22.00         |
| <b>SLR (IN)</b> | 24.8     | <b>ECE</b>     | E11-106R-007052 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12   | 17   | 23    | 29    | 35    | 41    | 46    | 52    | 58    | 65    | 73    | 80    | 87    |
|-----------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 40        | --   | --   | --    | 7440  | 8600  | 9750  | 10750 | 11740 | 12900 | 13720 | 14550 | 15540 | 16530 |
| 30        | --   | --   | --    | 9010  | 10410 | 11810 | 13010 | 14210 | 15610 | 16610 | 17610 | 18820 | 20010 |
| 25        | --   | 7430 | 9230  | 10120 | 11690 | 13270 | 14620 | 15970 | 17550 | 18670 | 19800 | 21140 | 22490 |
| 20        | 6250 | 8240 | 10240 | 11240 | 12980 | 14740 | 16240 | 17740 | 19480 | 20720 | 21980 | 23480 | 24970 |
| 15        | 6540 | 8630 | 10710 | 11760 | 13590 | 15420 | 16990 | 18550 | 20380 | 21690 | 22990 | 24560 | 26120 |
| 10        | 6820 | 9010 | 11190 | 12280 | 14190 | 16100 | 17740 | 19380 | 21280 | 22650 | 24010 | 25650 | 27280 |
| 5         | 7440 | 9820 | 12200 | 13390 | 15480 | 17560 | 19340 | 21130 | 23210 | 24700 | 26190 | 27980 | 29760 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.