


AGRIMAX V- FLECTO

TIRE SIZE	VF 710/70 R 42
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTEUR DE FORTE PUISSANCE / TRACTEUR
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	185 D



DIMENSIONS IS STANDARD

SW (MM)	715	RIM REC	DW 25 B
OD (MM)	2061	RIM ALT	DW 23 B; DW 24 B
SLR (MM)	909	ECE	E11-106R-006266
RC (MM)	6182	SRI	975

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6	2	2.4
70	3960	4545	5220	5895	6565	7240	7915	8415
FROM 65 TO 40	4350	4995	5735	6475	7215	7955	8695	9250
30	4435	5095	5850	6605	7360	8115	8870	9435
20	4525	5195	5965	6735	7505	8275	9045	9620
10	4785	5495	6310	7125	7940	8755	9565	10175
UPTO 30 CYC	4935	5670	6510	7350	8190	9030	9870	10495
UPTO 15 CYC	5890	6770	7770	8775	9775	10780	11780	12530
UPTO 10 CYC	6460	7420	8520	9615	10715	11815	12915	13735
10HT	4435	5095	5850	6605	7360	8115	8870	9435

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.