

# AS 504

<b>TIRE SIZE</b>	<b>27X10 - 15.3</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	TELESKOPLADER / FELD-ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE / TELESKOPLADER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	95 A8
<b>LI/SS FREE ROLLING</b>	107 A8



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94039500	<b>RC (IN)</b>	81.5
<b>SW (IN)</b>	10.2	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	27.4	<b>ECE</b>	E4-106R-002324
<b>SLR (IN)</b>	12.5	<b>PR</b>	8

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	45
5 FR	3010
15 FR	2560
20 FR	2400
25 FR	2150
5 DW	2130
15 DW	1810
20 DW	1710
25 DW	1520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.